

# Angle Touchless foaming soap dispenser, AC-powered K-25196

### **Features**

- Soap dispensing volume can be adjusted to 0.8 mL, 1.2 mL, 1.6 mL, or 2.0 mL.
- 54 oz. (1600 ml) high capacity soap reservoir.
- Optional 27 oz. (800 ml) low-capacity soap reservoir (sold separately).
- Sensor range adjustable from 1" to 4" (25.4 to 101.6 mm).
   Default set at approximately 2-3/4" (69.5 mm).
- Maintenance/cleaning mode is activated for 30 seconds when sensor is blocked for 10 seconds.
- Vandal-resistant sensor delays dispensing for twenty seconds if activated 4 times in under 5 seconds.
- Low soap above-the-counter indicator.
- Easy below-the-counter refill.
- AC-powered operation—no batteries to replace.
- Requires low (1-20 cps or gr/m-s) viscosity foam soap with no suspended particles. Please see Installation Guide or Maintenance and Use Guide for specific soap recommendations.
- Kohler Soap (sold separately) recommended for optimized performance and longevity.

#### Material

Cast brass construction for durability and reliability.

### Installation

 Optional deep rough-in mounting hardware kit for counters greater than 2" (50.8 mm) thick and less than 4-1/2" (114.3 mm) thick sold separately.

# **Required Products/Accessories**

K-13480-A AC Single Supply

or

K-13481-A Multi-Outlet Power Supply

### Recommended Products/Accessories

K-24879 Hollyhock-scented single-use foam soap refill – 800 ml  $\,$ 

K-24878 No fragrance/dye single-use foam soap refill – 1600 ml

K-24877 No fragrance/dye single-use foam soap refill – 800 mL

K-24882 No fragrance/dye foam soap refill – five gallons

K-24881 No fragrance/dye foam soap refill – one gallon

K-24880 Hollyhock-scented single-use foam soap refill – 1600 mL

## **Optional Products/Accessories**

K-25136 Soap reservoir - 800 mL



# Codes/Standards

None Applicable

# **KOHLER® One-Year Limited Warranty**

See website for detailed warranty information.

### Available Colors/Finishes

Color tiles intended for reference only.


**Color Code Description** 

CP Polished Chrome





# Angle Touchless foaming soap dispenser, AC-powered K-25196



# **Required Electrical Service**

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

120/240 V, 50/60 Hz

# **Technical Information**

All product dimensions are nominal.

Material: Brass

### **Notes**

Install this product according to the installation instructions.

