FRIGIDAIRE

AVAILABLE

COLORS

FFAD6022W1



SIGNATURE FEATURES

Easy-to-Clean Washable Filter

Capture dust from the air and keep your dehumidifier working efficiently with our easy-to-clean washable filter.

Continuous Drain Option

Skip emptying the water bucket -this unit continuously drains your dehumidifier so that you don't have to lift a finger.

Custom Humidity Control Maximize your comfort with customized control over the amount of humidity in your room.

Automatic Shut Off

Unit shuts off automatically when the water bucket is full.

Frigidaire High Humidity 60 Pint Capacity Dehumidifier

MORE EASY-TO-USE FEATURES

Front Loading Bucket with Carrying Handle and Splash Guard

A water bucket is conveniently located in the front of the unit for easy access, while the carry handle and splash guard make emptying your bucket hassle-free.

Portable Design

Easily move from room to room with caster wheels and side handles, dehumidifying your room when and where you need it.

Low Temperature Operation This unit is designed to operate at low temperatures down to 41°F.

Multi-Speed Fan Enjoy more cooling flexibility with two different fan speeds.

FFAD6022W1 Frigidaire High Humidity 60 Pint Capacity Dehumidifier

FRIGIDAIRE

General	Specifications
Ocherai	opeenications

Product Weight	59.9 lbs
Prop 65 Label	Yes
Warranty - Labor	1 Year
Warranty - Parts	1 Year
Power Type	Electric
Size	None
Installation Type	Free-Standing
Collection	Frigidaire
Performance	
Dehumidification - Pints per Day	60
Safety Certifications & Approvals	
UL Listed	Yes
cUL Listed	Yes
Energy Efficiency Verification (Canada)	Yes
Dimensions and Volume	
Height	24 3/5″
Width	18 25/32"
Depth	14 23/32"

Air CFM (Low)	245 CFM
Air CFM (High)	297 CFM
Fan Speeds - Fan	2
Noise Level dB (Low)	53 dB
Noise Level dB (High)	57 dB
Motor RPM (Low)	760 RPM
Motor RPM (High)	1,070 RPM
Container Capacity	21.1 pints
Container Full Indication	Yes
Digital Humidity Readout	Yes
Filter Access	Yes
Filter Check Indicator	Yes
Filter Type	Easy-to-Clean Washable Filte
Low Temperature Operation	Yes
stallation	
Power Cord Length	72"
ontrols	
Control Type	Electronic
unctions	
24-Hour On/Off Timer	Yes
Auto Restart	Yes
Auto Shut-Off	Yes
Continuous Drain Operation	Yes
lectrical Specifications	
Plug Type	LCDI 515P
Voltage Rating	115 V

Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com / frigidaire.ca. Specifications subject to change. Accessories information available on the web at frigidaire.com / frigidaire.ca



USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidaire.com CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca

FFAD6022W1 ©2017 Electrolux Home Products, Inc.