

# **TECHNICAL DATA**

TAMPER BT 60, BT 65





Maximum reliability and longevity
All around engine protection



More transparency
Hour counter/tachometer with a
service indicator which can be reset



**Simple operation**Engine and fuel supply with combined switch

#### Shipping dimensions in cub.yd

**BT 60** 0.345 **BT 65** 0.345



# **Standard Equipment**

- ☑ Engine Protection System -Protective engine covering -Paper air filter system with two stages
  - -Automatic oil level control -Dual fuel filter system
- ☑ Vibration insulated steering bow
- ✓ Self-cleaning air filter housing
  ✓ Self-cleaning air filter housing
  ✓ Protective covering
  ✓ Single point lifting device
  ✓ Recoil starter

- ✓ Plastic castor as loading aid
- ✓ Infinitely variable frequency
   ✓ Combination of engine stop/fuel switch
- ✓ h-/ rpm meter✓ 3-2-1 Warranty

### **Optional Equipment**

- ☐ Transport device with puncture proof wheels
- ☐ Tamper foot widths (6.3-13 in)
- ☐ Tamper foot extensions
- ☐ Special painting ☐ Tool kit
- $\hfill\Box$  Service Kit
- □ Operator protection contact breaker switch

  ☐ TOUGH WARRANTY

# Dimensions in inch

R Н L1 W

**BT 60** 13.8 40.6 28.7 13.2 9.1 **BT 65** 13.8 40.6 28.7 13.2 11.0

Technical Data		BOMAG BT 60	BOMAG BT 65
Weights Operating weight CECE		128 126	150 148
Dimensions Working width (tamper plate)	in	11.0	11.0
Driving Characteristics Working speed max		65.6 2,970.9	65.6 3,616.8
Drive Engine manufacturer Type Emission stage Cooling Number of cylinders Performance SAE J 1349 Performance SAE J 1349 Fuel Drive system Fuel comsump. aver. during operation	kW hp	Honda GXR 120 StageV/CARB P.3 air 1 2.8 3.8 Gasoline mech. 0.2	Honda GXR 120 StageV/CARB P.3 air 1 2.8 3.8 Gasoline mech. 0.2
Exciter system Frequency Impact force		600.0-708.0 3,372	600.0-708.0 3,822
Capacities Fuel Technical modifications reserved. Machines may be shown with options.	gal	0.8	0.8



**BOMAG Americas, Inc.** 125 Blue Granite Parkway Ridgeway, SC 29130 USA Tel. +1 803 3370700 Fax +1 803 3370800 www.bomag.com/us

