# The Classic Vacuity® Floor-Mounted Back-Outlet















Dimensions may vary (+) or (-) 1/4". Dimensions shown in parentheses are in millimeters: 25.4 mm = 1 inch. Note: Fixture dimensions are nominal and conform with dimension and performance requirements of ASME/ANSI Standards A112.19.2M. Dimensions subject to change or cancellation without notice. Briggs is not responsible for the use of superseded or voided specification information.

## **FEATURES**

- Stain-resistant vitreous china
- Floor-mounted for commercial applications
- Powerful one-flush performance of PowerVAC<sup>™</sup> flushing system
- 10" x 12" water surface
- High quality Fluidmaster® tank fittings
- Operates in a wide range of pressure (5 PSI to 100 PSI)
- · Sanitary bar on bowl for ease of cleaning
- Tank within a tank eliminates condensation
- Color-matched trip levers
- 10-year PowerVAC Advantage<sup>™</sup> warranty

## **AVAILABLE COLORS**



## **SPECIFICATIONS**

 Model 4245: 12" rough-in elongated, floor-mounted, back-outlet toilet, 97 lb, consists of bowl (Model 4345) and tank (Model 4400)

## **OPTIONS**

- Model 4401: 12" rough-in tank and lid w/ lid lock, 40 lb
- Model 4408: 12" rough-in tank and lid w/ right-hand lever, 40 lb
- Model 4408L: 12" rough-in tank and lid w/ right-hand lever and lid lock, 40 lb
- Model 7444: Tank lid for Model 4400 and 4408, 12 lb
- Model 7445: Tank lid for Model 4401, 12 lb

## INSTALLATION

- Installation instructions supplied
- Quick-connect system for easy tank-to-bowl installation

**₿BRIGGS**®

(800) 888-4458

www.briggsindustries.com

Design | Technology | Innovation