

General Tank Cross Features:

- Internal and external threads reduce fittings needed and installation time.
- Reduces turbulence and waterlogging in tanks without separate air chambers.
- Injected molded PVC, galvanized ductile iron.
- Crosses are **third party certified to NSF/ANSI 372**.



Short Cast Crosses with 1 drain and 3 top ports.


*** DO NOT USE PTFE THREAD SEAL TAPE WITH PVC TANK CROSS APPLICATIONS. USE THREAD SEAL PASTE WITH OUT PTFE FOR PLASTIC THREADS ONLY.**



Part Number	Overall Length	Tank Conn.	Leg Conn.	Drain Ports Size (Qty)	Top Ports Size (Qty)	Material	USA or Import	Ctn Qty
CIC125	4 1/4"	1 1/4" x 1"	1" x 3/4"	3/4" (1)	1/4" (2), 1/2" (1)	PVC*	USA	100



Short cast galvanized crosses with one drain, two top ports



Part Number	Overall Length	Tank Conn.	Leg Conn.	Drain Ports Size (Qty)	Top Ports Size (Qty)	Material	USA or Import	Ctn Qty
HC100G	3 3/4"	1" (FIP)	1" (FIP)	1/2" (1)	1/4" (2)	Ductile Iron	Import	30
HC10075G	4"	1" (FIP)	1" (FIP)	3/4" (1)	1/4" (2)	Ductile Iron	Import	40
HC125G	3 3/4"	1 1/4" (FIP)	1 1/4" (FIP)	1/2" (1)	1/4" (2)	Ductile Iron	Import	24
HC12575G	4"	1 1/4" (FIP)	1 1/4" (FIP)	3/4" (1)	1/4" (2)	Ductile Iron	Import	25



Short cast galvanized crosses with one drain, two top ports



Part Number	Overall Length	Tank Conn.	Leg Conn.	Drain Ports Size (Qty)	Top Ports Size (Qty)	Material	USA or Import	Ctn Qty
IC100G	3"	1" (FIP)	1" (FIP)	3/4" (1)	1/4" (2)	Ductile Iron	Import	28
IC125G	3 1/2"	1 1/4" (FIP)	1 1/4" (FIP)	3/4" (1)	1/4" (2)	Ductile Iron	Import	24



Short cast galvanized crosses with two drain, two top ports



Part Number	Overall Length	Tank Conn.	Leg Conn.	Drain Ports Size (Qty)	Top Ports Size (Qty)	Material	USA or Import	Ctn Qty
IC200G	3"	1" (FIP)	1" (FIP)	1/2" (2)	1/4" (2)	Ductile Iron	Import	48