



PSC Series




Poly-Stretch Repair Coupling Features:

- For repair of polyethylene irrigation pipe.
- Avoid extra digging and buckled pipe.
- Couplings are made of ABS
- O-ring seal is made of Buna 70
- Pressure rated at 160 psi.
- Designed for irrigation operation pressures of polyethylene pipe and more.

Instructions for Installation:

- Cut out approximately 4" of pipe where repair is needed.
- Place clamps over ends of pipe
- Insert end marked with "END FIRST" arrow by pushing and turning at same time.
- Insert other end by pushing & turning.
- Place clamps over ribbed ends & tighten.

Dimensions:



	A	B	C	D	E
3/4"	4.0	.575	.820	1.50	5.625
1"	4.0	.770	1.075	1.50	5.625
1 1/4"	5.0	1.109	1.415	1.755	6.70
1 1/2"	5.0	1.310	1.63	1.755	6.70
2"	5.0	1.825	2.125	1.755	6.70

Part

Part Number	Description	Ctn Qty
PSC07	3/4" Poly-stretch coupling	50
PSC10	1" Poly-stretch coupling	50
PSC12	1 1/4" Poly-stretch coupling	25
PSC15	1 1/2" Poly-stretch coupling	25
PSC20	2" Poly-stretch coupling	20