



▲ Designate proper finish suffix

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Delta can do

BATHROOM FAUCET

■ Single Handle Deck Mount

STANDARD SPECIFICATIONS

- Max flow rate 1.2 gpm @ 60 psi, 4.5 L/min @ 414 kPa
- · Solid metal fabricated body
- One or three hole mount (escutcheon included)
- Polymer braided flexible supply hose with 3/8" compression fitting
- Control mechanism is replaceable cartridge with ceramic plates
- 1/2"-14 NPSM adapters
- · Spring loaded pop-up included with drain plug

WARRANTY

- · Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.)
- Electronic Parts and Batteries (if applicable) 5 years from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.); or for commercial purchasers, 1 year from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.). No warranty is provided on batteries.
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A 112.18.2 / CSA B 125.2
- EPA WaterSense®

人 ICC/ANSI A117.1 - Valve control only

Delta Faucet Company
FE F 111th Street, Carmel, IN 46280 55 E. 111th Street, Carmel, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2024 Delta Faucet Company