

Specifications

ARM5884

Insulated A6 Nitrile Dipped Glove



Product Features

- Sandy Nitrile Palm Coating
- 13 Gauge HPPE Outer Liner
- 10 Gauge Acrylic Inner Liner
- ANSI A6 Cut Level
- ANSI Impact Level 2
- Reinforced Thumb
- Contact Cold Protection
- Liner: High-Performance Polyethylene (HPPE) + Acrylic
- Coating: Nitrile
- TPR: Thermo Plastic Rubber
- Cuff: HPPE, Acrylic and Latex Elastic



| SPECIFICATIONS | |
|----------------|------|
| SKU | Size |
| ARM5884S | 7 |
| ARM5884M | 8 |
| ARM5884L | 9 |
| ARM5884XL | 10 |
| ARM5884XXL | 11 |

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

- 1 Pair on Hangtag
- 6 Pairs in Polybag
- 60 Pairs in Case

Testing Performance

ANSI/ISEA 105

| | | | | | | | | | |
|----------|---|---|---|---|---|---|---|---|---|
| Cut | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| Abrasion | 1 | 2 | 3 | 4 | 5 | 6 | | | |
| Puncture | 1 | 2 | 3 | 4 | 5 | | | | |

ANSI/ISEA 138

| | | | |
|--------|---|---|---|
| Impact | 1 | 2 | 3 |
|--------|---|---|---|

EN388

| | | | | | | |
|--------------------|---|---|---|---|---|---|
| Abrasion | 1 | 2 | 3 | 4 | | |
| Circular Blade Cut | 1 | 2 | 3 | 4 | 5 | X |
| Tear | 1 | 2 | 3 | 4 | | |
| Puncture | 1 | 2 | 3 | 4 | | |
| Cut TDM-100 | A | B | C | D | E | F |
| Impact Rated | P | F | X | | | |

EN511:2006 – X2X

| | | | | | |
|-------------------|---|---|---|---|---|
| Convective Cold | 1 | 2 | 3 | 4 | X |
| Contact Cold | 1 | 2 | 3 | 4 | X |
| Water Penetration | 0 | 1 | X | | |