

26 726

EUPHORIA®

310 COOLTOUCH THERMOSTATIC SHOWER SYSTEM

Pure Freude
an Wasser



STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE CoolTouch® no risk of scalding
- GROHE TurboStat® compact cartridge with wax thermostatic element
- Exposed thermostatic temperature control with SafeStop® at 100°F / 38°C
- GROHE SafeStop Plus optional temperature limiter at 110°F (43°C) included
- GROHE DreamSpray perfect spray pattern
- GROHE EcoJoy 1.75 gpm (6.6 l/min) flow limiter
- 17 ¾" Horizontal swivel shower arm
- GROHE QuickFix® (upper bracket adjustable)
- Switch between hand shower and shower head via built-in diverter
- 2 Discrete functions (non-shared)
- Bar with adjustable height hand shower holder
- Includes adaptors for easy installation (depth adjustable)
- 69" Rotaflex metal shower hose (1750mm) (28 025)
- ADA compliant handles
- CALGreen compliant
- Speed Clean® anti-lime system
- Rainshower™ Mono 310 shower head
- Spray: GROHE PureRain
- Euphoria 110 hand shower (26 513), 1.75gpm
- 3 Adjustable sprays: Rain, Massage & SmartRain
- Protected against backflow
- Optional: GROHE EasyReach tray (26 362 LN1) (sold separately)
- Optional: Spacer Disc ¼" (27 180) (sold separately)
- Optional: Longer Rail 46" (1166mm) (48 053) (sold separately)
- Optional: Shorter Rail 34" (866mm) (48 054) (sold separately)
- Optional: Service Stop (12 400) (sold separately)



PRODUCT FEATURES:

- GROHE CoolTouch®
- GROHE DreamSpray®
- GROHE EcoJoy™
- GROHE QuickFix®
- SafeStopPlus
- GROHE TurboStat®
- GROHE StarLight®

CERTIFICATIONS:



- WaterSense
- CEC Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- ASSE 1016
- CSA B125.1
- CSA B125.16
- ASME A112.18.1
- ASME A112.1016

AVAILABLE FINISHES:

26726000



GROHE StarLight®
Chrome

26726E00



Brushed Nickel
InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

Tel: 1.630.582.7711 Fax: 1.630.582.7722

We reserve the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.grohe.us.

02-10-2021

PART OF **LIXIL**

26 726

EUPHORIA®

310 COOLTOUCH THERMOSTATIC
SHOWER SYSTEM

Pure Freude
an Wasser



TECHNICAL DATA:

Product Height

GPM (Min)-GPM (Max)

1.75 GPM

