

AE2820



SERIES
AE2800
ALUMINUM EXTENSION LADDER

TYPE IA
300 LBS. LOAD CAPACITY
INCLUDES WEIGHT OF USER PLUS MATERIALS

RAIL DEPTH

3"

RAIL DEPTH

6"

INSIDE WIDTH

base 15 1/4"

fly 15 3/4"

OUTSIDE WIDTH

base 18"

fly 18"

► *D-shaped rungs



1. Mar-resistant rail end caps.
2. QuickLatch™
3. D-shaped rungs.



4. Stacked aluminum I-beam rail.
5. Rubber fly section shoes.
6. Swivel safety shoes.

MODEL	TOTAL LENGTH	LENGTH EACH SECTION	MAX. EXTENDED LENGTH	MAX. REACH	APPROX. WEIGHT (LBS)	APPROX. CUBES
AE2816*	16'	8'	13'	15' 11"	32	6.3'
AE2820	20'	10'	17'	19' 10"	39	9.5'
AE2824	24'	12'	21'	23' 8"	46	11.4'
AE2828	28'	14'	25'	27' 7"	59	13'
AE2832	32'	16'	29'	31' 5"	66	15.2'
AE2836	36'	18'	32'	34' 4"	80	16'
AE2840	40'	20'	35'	37' 3"	89	16.8'

► *Does not include rope or pulley

AE3220



SERIES
AE3200
ALUMINUM EXTENSION LADDER

TYPE I
250 LBS. LOAD CAPACITY
INCLUDES WEIGHT OF USER PLUS MATERIALS

RAIL DEPTH

3"

STACK HEIGHT

5 1/4"

INSIDE WIDTH

base 15 1/4"

fly 13 15/16"

OUTSIDE WIDTH

base 17 1/2"

fly 16 3/16"

MAXLOCK™

► *D-shaped rungs



1. Mar-resistant rail end caps.
2. D-shaped rungs.
3. Modified I-beam.



3. MaxLock™ with QuickLatch™.
5. Swivel safety shoes.

MODEL	TOTAL LENGTH	LENGTH EACH SECTION	MAX. EXTENDED LENGTH	MAX. REACH	APPROX. WEIGHT (LBS)	APPROX. CUBES
AE3216*	16'	8'	13'	15' 11"	27	7.1'
AE3220	20'	10'	17'	19' 10"	32	8.9'
AE3224	24'	12'	21'	23' 8"	38	10.6'
AE3228	28'	14'	25'	27' 7"	53	12.3'
AE3232	32'	16'	29'	31' 5"	60	14'
AE3236	36'	18'	32'	34' 4"	72	15.7'
AE3240	40'	20'	35'	37' 3"	80	17.4'

AE4110



SERIES
AE4100
ALUMINUM SINGLE LADDER

TYPE II
225 LBS. LOAD CAPACITY
INCLUDES WEIGHT OF USER PLUS MATERIALS

RAIL DEPTH

3"

INSIDE WIDTH

15 1/4"

OUTSIDE WIDTH

17 1/8"

► *D-shaped rungs



1. Mar-resistant rail end caps.
2. D-shaped rungs.



3. Modified I-beam.
4. Swivel safety shoes.

MODEL	TOTAL LENGTH	MAX. REACH	APPROX. WEIGHT (LBS)	APPROX. CUBES
AE4110	10'	13'	17	5.8'
AE4112	12'	15'	20	6.9'
AE4114	14'	16' 11"	23	8'
AE4116	16'	18' 10"	29	9.1'
AE4118	18'	20' 9"	31	10.3'
AE4120	20'	22' 8"	36	11.4'