

S11967

30T8/LED/72-865/BP/R17D/HO

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	30WW
Color Temperature:	6500K
Length:	70"
Base:	Recessed Double Contact HO/VHO

TECHNICAL SPECIFICATIONS

Wattage:	30W
Volts:	120V-277V
Fluorescent Equivalent:	87W
Shape:	T8
Filament:	LED
Base:	Recessed Double Contact HO/VHO
ANSI Base:	R17d
Finish:	Frost
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	6500K
CRI:	82CRI
Lumen Output:	4200L

Dimmable:	Non-Dimmable
Beam Spread:	160D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	BallastBypass
Ballast Type:	Type B
Single / Dual End:	Double Ended
Tube Guard Use:	Yes
Safety Listing:	cULus
Technology:	LED
Material:	Glass

DIMENSIONS

MOL:	70"
MOD:	1.1"
Weight:	1.01

LISTINGS

Safety Listing:	cULus
Location Rating:	Damp
Energy Star:	No
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119675
Each Quantity:	1
Each Dimensions:	72.00 x 1.10 x 1.10"

Case UPC:	10045923119672
Case Quantity:	10
Case Dimensions:	74.60 x 7.87 x 4.92"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2021
Satco Products, Inc.
All Rights Reserved
July 16, 2021