

Barlow LED Vanity BARV Series

Features

Decorative vanity with a frosted acrylic diffuser. Ideal use for general lighting in indoor residential, commercial, and hospitality applications. Fixture can be mounted horizontally or vertically to a 2" \times 4" junction box (not included) or a 4" \times 4" box with included cover plate (shown on SN*).

Construction

Fabricated metal housing. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black, polished chrome, satin brass or satin nickel finish.

Diffuser

Frosted acrylic diffuser.

Electrical

Input 120 VAC 60 Hz.

Compatible with residential TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing:

18" - 20W = 1800 source lumens, 1000 delivered lumens

24" - 22W = 2600 source lumens, 1125 delivered lumens

36" - 30W = 3800 source lumens, 1634 delivered lumens

3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.

Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.


Specifications and dimensions subject to change without notice.











Ordering Information:

Black	Polished Chrome	Satin Brass	Satin Nickel	LED	Lumens	Lumens	CCT	L	Н	D
BARV1803L30D1BK	BARV1803L30D1PC	BARV1803L30D1SB	BARV1803L30D1SN	20W	1800	1000	3000K	18"	3"	2-1/4"
BARV2403L30D1BK	BARV2403L30D1PC	BARV2403L30D1SB	BARV2403L30D1SN	22W	2600	1125	3000K	24"	3"	2-1/4"
BARV3603L30D1BK	BARV3603L30D1PC	BARV3603L30D1SB	BARV3603L30D1SN	30W	3800	1634	3000K	36"	3"	2-1/4"

Source Delivered