

FaciliPro™ Taj Mahal™

Page 1 of 2

CLASSIFICATION

Combination Floor Sealer and Finish

PRODUCT DESCRIPTION

FaciliPro™ Taj Mahal™ provides excellent adhesion, abrasion resistance and detergent tolerance. The product is ideal for terrazzo, concrete or resilient floors.

USE

FOR INDUSTRIAL USE ONLY
KEEP FROM FREEZING

Uses:

- Ideal for terrazzo flooring.
- Works well with both resilient and non-resilient flooring.

Features and Benefits:

- 20% solids content.
- FaciliPro™ Taj Mahal™ provides strong floor adhesion.
- The product yields a high-gloss finish.
- It is tolerant to detergents.
- FaciliPro™ Taj Mahal™ is also an excellent pore sealer; the use of a separate sealer is not required on most floors.
- It may also be used as a removable base coat.
- Product meets CARB VOC threshold to help reduce air pollution.
- Product meets or exceeds the CSMA benchmark for slip resistance as determined by ASTM D-2047.



FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE ONLY 95Y7
REVÊTEMENT POUR PLANCHERS ET MATÉRIAU DE FINITION POUR UNE
RÉSISTANCE AU GLISSEMENT UNIQUEMENT 95Y7
MATERIAL DE ACABADO Y REVESTIMIENTO DEL SUELO EN CUANTO A
RESISTENCIA A DESLIZAMIENTOS SOLAMENTE 95Y7

Directions for General Use

Full Strip Preparation: Strip the floor with an Ecolab stripper at the recommended use dilution. Rinse well and let dry.

Scrub and Recoat Preparation: Deep scrub with an Ecolab alkaline cleaner using a green or blue pad. Rinse and let dry.

Sealing the Floor: FaciliPro™ Taj Mahal™ is an excellent pore sealer; the use of a separate sealer is not required on most floors. If a sealer is desirable for resistance against staining spills, use an Ecolab sealer according to label directions.

Application: FaciliPro™ Taj Mahal™ may be applied from either thin to heavy coats depending on the application technique.

Coverage: FaciliPro™ Taj Mahal™ usually covers 2000 to 4000square feet/US gallon (185 to 371 square meters/3.78 liters).

Maintenance

- Dust mop and damp mop or auto scrub daily with an Ecolab recommended cleaner.
- Buff or burnish 1 to 3 times per week.
- Prepare the floors with an Ecolab cleaner/maintainer prior to buffing or burnishing to enhance the gloss response.

FaciliPro™ Taj Mahal™ expires 1080 days from the manufacturing date.

The product is not freeze/thaw stable.

Store between 50°F (10°C) and 104°F (40°C).

For service or additional information, call 1-800-35-CLEAN (352-5326).

PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid [Emulsion]
Color: White, Opaque
Odor: Acrylic-like
PH: 7.0 – 8.2 [Conc. (% w/w): 100%]

INGREDIENTS:

Chemical Name/CAS (if present)	Percentage
2-(2-ethoxyethoxy)ethanol, 111-90-0	1 - 5
Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol, 25265-77-4	1 - 5

% P: Formula contains trace amounts of elemental phosphorus.

PACKAGING/PRODUCT NUMBERS

Size Available	Product Number
2 X 2 U.S. gallon/7.57 liter (Phazer)	6100761
2.5 U.S. gallon/9.46 liter	6114631
5 U.S. gallon/18.9 liter	6102148