

PRODUCT DATA SHEET

RTP™ SERIES

Condensate Removal Tank Pumps

A CSW Industrials Company

Description

The RTP (RectorSeal Tank Pump) series is designed as an automatic condensate removal pump for heating and air conditioning systems. The pump is controlled by a float switch mechanism which turns the pump on when approximately 2¼" of water collects in the tank, and automatically switches off when the tank drains to approximately 1½".



Packaging

Code	Description	Qty per Case	Lbs per Case	Cubic Feet
83885	RTP15-110	10	57.3	3.57
83887	RTP24-110	10	57.3	3.57
83888	RTP24-230	10	57.3	3.57

Applications

Air conditioners, furnaces and dehumidifiers, residential or commercial

Characteristics | Features

- ½ gallon high impact ABS tank for durability
- Float arm design for reliable operation
- 3 inlet drain holes for easy drain hose access
- · Compact design for easy installation
- 6 foot power cord to easily position pump
- 10 inch wires to connect pump to furnace or air handler for system shutoff capability
- Thermal overload protection
- Removable 3/8" check valve
- 3-year limited warranty

Specifications

Product code	Model Name	Volts	Hertz	Running		Gallons/Liters Per Hour at Height		Chuteff	
				Amps	Watts	1 ft / .3m	5 ft / 1.5 m	9 ft / 2.7 m	Shutoff
83885	RTP15-110	110	60	1	60	66 gph; 250 lph	53 gph; 200 lph	40 gph; 150 lph	15 ft / 4.6 m
83887	RTP24-110	110	60	2.2	110	153 gph; 580 lph	137 gph; 520 lph	124 gph; 470 lph	24 ft / 7.3 m
83888	RTP24-230	230	50/60	1.3 / 1.1	125 / 110	140/153 gph; 530/580 lph	127/137 gph; 480/520 lph	111/124 gph; 420/470 lph	24 ft / 7.3 m

Manufactured for

RectorSeal, LLC