

59-300 Series

Bronze Wye-Strainer



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

DESCRIPTION

The Apollo 59-300 Series Heavy Pattern Strainers are designed with large area screens to protect piping systems and process equipment from unwanted foreign particles with minimum pressure loss.

FEATURES

- 100% Factory Pressure Tested
- Self-Aligning Screen Design
- Numerous Mesh and Blow-Off Options Including Blow-Off Ball Valves
- **Made in USA**

APPROVALS

- CRN OE8959.5

PERFORMANCE RATING

- Working Pressure:
CWP: 400 psi
SWP: 125 psi
- Maximum Temperature: 350° F

MODELS

- (59000) Female NPT Connection
- (59LF000) Lead Free Female NPT Connection
- (59FL300) Lead Free Solder Connection (1/2" - 3")

OPTIONS

- (-E1) - 20 Mesh
- (-O1) - Plain Cap
- (-B1) - 60 Mesh
- (-C1) - 80 Mesh
- (-H1) - 100 Mesh
- (-O2) - Tapped Cap
- (-P2) - Tapped Cap with Plug
- (-O6) - Tapped cap with Ball Valve

STANDARD MATERIALS LIST

BODY	Cast Bronze, ASTM B584
CAP	Brass, ASTM B16 (1/2" - 1") Brass, ASTM B584 (1-1/4" - 3")
SCREEN	Stainless Steel, 304
O-RING (1/2")	PTFE
GASKET (3/4" - 3")	PTFE

DIMENSIONS

PART NUMBER	SIZE (IN.)	LENGTH (IN.)	CAP TAPPING (-O2 SUFFIX)	NET SCREEN AREA (IN²)	WT. (LB.)
59-303	1/2	2.75	1/4 NPT	3.2	0.50
59-304	3/4	4.00	1/2 NPT	6.7	1.21
59-305	1	4.75	3/4 NPT	10.8	1.89
59-306	1-1/4"	5.25	3/4 NPT	13.5	2.80
59-307	1-1/2	6.00	1 NPT	19.0	4.26
59-308	2	7.25	1-1/4 NPT	27.6	6.27
59-309	2-1/2	9.58	1-1/4 NPT	41.0	11.17
59-310	3	10.58	1-1/2 NPT	56.0	16.48

STANDARD SCREENS

SIZE (IN.)	SCREEN
1/2	50 Mesh
3/4 to 3	20 Mesh

FLOW CURVES

