



S29917

40T8/LED/96-835/BP/FA8

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	40WW
Color Temperature:	3500K
Length:	94.00"
Base:	Single Pin



TECHNICAL SPECIFICATIONS

Wattage:	40W
Volts:	120V-277V
Fluorescent Equivalent:	59W
Shape:	T8
Filament:	LED
Base:	Single Pin
ANSI Base:	FA8
Finish:	White
Hours Rated:	50000H
Color Temperature:	3500K
CRI:	82CRI
Lumen Output:	5300L

Dimmable:	Non-Dimmable
Beam Spread:	210D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Double Ended
Shatter Proof Type:	PET Coated
Safety Listing:	cULus
Technology:	LED
Material:	Glass

DIMENSIONS

MOL:	94.00"
MOD:	1.00"
Weight:	0.88

LISTINGS

Safety Listing:	cULus
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLSDLWQ3P1GE
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923299179
Each Quantity:	1
Each Dimensions:	94.00 x 1.00 x 1.00"

Case UPC:	10045923299176
Case Quantity:	10
Case Dimensions:	95.87 x 7.56 x 3.86"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2021
Satco Products, Inc.
All Rights Reserved
November 17, 2021