



F6-BOOST™

BLDC IGNITION-PROOF REFRIGERANT RECOVERY MACHINE

Designed for Speed and Reliability: **F6-BOOST Powers Through Every Job.**

The **F6-BOOST Refrigerant Recovery Machine** provides users over 20% faster recovery rates than competitor models. The unique 2-cylinder, oilless compressor and long-lasting pistons are contained in a light-weight ergonomically designed, easy-to-use unit. Experience fast and reliable refrigerant recovery of AHRI groups III, IV, and V refrigerants.

20%^{OVER}
FASTER
THAN COMPETITION

TESTED FOR SAFETY

- Ignition-proof design tested to UL12.12.01 as specified by UL1963 Supplement SB for A2L refrigerants

FAST & POWERFUL

- Universal voltage (100-240VAC 50/60Hz)
- Powerful 1.25 HP BLDC Brushless DC motor driven oilless compressor
- High air flow fan with a micro-channel condenser to keep the unit running cool
- Variable speed motor (based on load)
- 2-cylinder oilless piston design with durable, long-lasting elastomer seals that are easy to replace

ESSENTIAL FEATURES

- Pressurized sealed crankcase prevents refrigerant loss and protects bearings from liquid refrigerant damage
- Built in purge functionality (self clearing or pump down) to prevent cross contamination
- High pressure 550 PSIG cutout switch
- Auto shut-off upon recovery completion with status indicator light
- Compact light-weight 23.5lb unit with robust, high-impact, injection-molded case
- Optional tank overfill cord available
- Recessed folding handle with rubber grip and padded shoulder strap
- 10' locking power cable and velcro cord wrap
- 1 year OTC; 2-year repair and return warranty



10' locking power cable and
Velcro cord wrap



Rugged recessed handle for storage



FOLLOW US!



JB INDUSTRIES

800.323.0811 JBIND.COM SALES@JBIND.COM