

Thermo-Gard  
Surface Mounted  
Nominal 6" x 8"



### Specifications

**Lens/Housing:** One-piece wraparound lens/housing (U.V. stabilized, high impact, virgin injection molded polycarbonate). Pearlescent, clear or prismatic lens. Nominal thickness .125".

**Baseplate:** 16-gauge CRS. Baseplate provided with four-point mounting holes. White urethane powder coat finish.

**Hardware:** Two stainless steel POSIGRIP™ fasteners secure lens/housing to baseplate.



**Installation:** Standard four-point mounting required for Peace of Mind Lifetime Guarantee™.

## PEACE OF MIND

### Lifetime Guarantee™

Kenall high abuse Thermo-Gard covers are designed and built to take exceptional physical punishment. When installed according to our instructions, Kenall will replace any cover broken during the life of the cover.

### Dimensional Data



#### Maximum Thermostat Dimensions

|        |                       |
|--------|-----------------------|
| TG-1,2 | 5"x2 7/8"x3 1/8" Deep |
| TG-37  | 5 1/2"x3"x3 1/8" Deep |

### Easy Installation



**Step 1**  
Install Thermostat



**Step 2**  
Install Frame



**Step 3**  
Install Lens

### Features

**Versatile:** Two sizes available to fit over most thermostats.

**Easy to Install:** Install Thermo-Gard without removing your thermostat from the wall.

**Fast Thermal Response:** Construction allows air to circulate freely so there is only a 1-1/2 minute lag in thermostat response.

**Securely Mounted:** Steel frame is firmly attached to wall with screws (furnished). Cover cannot be pried off.

**Tough:** Made of virgin U.V. stabilized, high impact, injection molded polycarbonate. Will take full hammer blow or the impact of a .22 caliber bullet.

**Shock-Resistant:** Unique mounting system protects your thermostat from shock or breakage.

**Tamper-Resistant:** Mounts to its own back frame with two stainless steel POSIGRIP™ screws to keep unauthorized people out.

**Vandal-Resistant:** 1/8" holes in guard prevent foreign objects such as knives or pencils from being inserted to damage thermostat.

### Ordering Information

| Catalog Number | Description  | Cover       | POSIGRIP™ Screw (Qty) | Cover Dimensions |           |           | Pack | Wt. (Lbs.) |
|----------------|--|-------------|-----------------------|------------------|-----------|-----------|------|------------|
|                |  |             |                       | (A) Height       | (B) Width | (C) Depth |      |            |
| TG-1           | Thermostat cover; two POSIGRIP screws                  | Pearlescent | 2                     | 7.750"           | 5.375"    | 4.250"    | 6    | 1.3        |
| TG-1J          | Same as TG-1 except for use with junction box mounting | Pearlescent | 2                     | 7.750"           | 5.375"    | 4.250"    | 6    | 1.3        |
| TG-2           | Thermostat cover; two POSIGRIP screws                  | Clear       | 2                     | 7.750"           | 5.375"    | 4.250"    | 6    | 1.3        |
| TG-2J          | Same as TG-2 except for use with junction box mounting | Clear       | 2                     | 7.750"           | 5.375"    | 4.250"    | 6    | 1.3        |
| TG-37          | Thermostat cover; two POSIGRIP screws                  | Prismatic   | 2                     | 8.500"           | 5.875"    | 4.125"    | 6    | 2.0        |