

# QDS-0301 SPECIFICATIONS

## INOX deck-mount spout

### FEATURES:

- Single-hole, deck-mount swiveling spout
- 6½" spout projection
- ¾" NPT connection
- Durable finish and sleek design
- Stainless steel AISI316L
- Brushed stainless steel (-AS) finish as standard
- Spout supports tubfiller application (requires aerator QPT-0002)
- Less drain, recommend, push-button waste QTW-0120 or QTW-0121



### SPECIFICATIONS:

Warranty:	Limited lifetime warranty (residential) One year warranty (commercial)
Material:	Stainless steel AISI316L
Finishes:	PVD: Physical Vapor Deposition PC: Powder Coat
Connection:	¾" NPT connection
Flow Rate:	1.2 gpm @ 60 PSI

### FINISH + COLOR (special order):

-black (PVD)	● -ON
-gold (PVD)	● -OC
-rose gold (PVD)	● -OR
-matte black (PC)	● -MB

### RECOMMEND (sold separately):

- Deck mixer handles: QTH-2051, QTH-2051V, QTH1751, QTH-1751V, QTH-1752, QTH-1752V, QTH1651, QTH-1651V, QTH-1652, QTH-1652V, QTH1251, QTH-1251V
- Tubfiller application requires QPT-0002 aerator (free flow)
- Push-button waste QTW-0120 or QTW-0121

### INSTALLATION:

Install this product according to the installation guide. Our products must be installed by certified professionals only and according to our installation guide as well as federal, provincial state and local building codes and regulations.

### CARE AND MAINTENANCE:

See Installation Manual

### CODES / STANDARDS APPLICABLE:

- Meets or exceeds ANSI / ASME standard A112.18.1 and CAN / CSA B125.1-05 requirements
- Listed with IAPMO bearing the UPC / cUPC mark
- ADA compliant
- Calgreen compliant
- California AB1953 compliant



\*Approximate measurements for comparison only.  
Note: These dimensions and specifications are subject to change without notice.

