




Tapcon Anchor

INSTALLATION INSTRUCTIONS

Read installation instructions before using!

| | | |
|---|--|---|
|  | <p>WARNING!</p> | <p>If there are any questions concerning proper installation, applications or appropriate use of this product, please call our Technical Services Department at 1-800-899-7890. Failure to follow these instructions can result in serious personal injury.</p> |
| <p>1.</p> | <p>Select proper fastener – diameter/head style/length.</p> | |
| | <p>a) Use selection chart to choose proper length.</p> | |
| <p>2.</p> | <p>Drill Hole – use selection chart to determine drill bit length and depth of hole.</p> | |
| | <p>a) Choose appropriate drill bit based upon diameter of Tapcon Anchor.</p> | |
| | <p>b) Drill hole minimum ¼" deeper than Tapcon Anchor to be embedded.</p> | |
| | <p>Minimum anchor embedment: 1"</p> | |
| | <p>Maximum anchor embedment: 1-3/4"</p> | |
| <p>3.</p> | <p>Drive Anchor.</p> | |
|  | <p>WARNING!</p> | <p>Failure to wear safety glasses with side shields can result in serious personal injury. Always wear ANSI compliant eye protection (ANSI Z87.1-2003).</p> |
|  | <p>WARNING!</p> | <p>Using the wrong size drill bit will affect performance values and may cause failure.</p> |