THE WORLD LEADER IN CLEAN AIR SOLUTIONS

DISPOSABLE FIBERGLASS MEDIA PANEL FILTERS

- Economically and environmentally friendly chipboard frame
- One-piece frame design eliminates corner separation
- Self-retaining media pack does not require metal support
- Hot-melt sealant around perimeter on both sides
- Fiberglass media
- Available in 1" models
- Available in all standard sizes, custom sizes also available
- UL Classified

Heavy-Duty Construction

The EZ Flow II filter is made to function without a retainer by adhering the frame directly to the media, which has a light skin to make it self-supporting. The EZ Flow II frame is made from heavy chipboard in a one-piece design that eliminates corner separation. Sealing is accomplished with a resilient hot-melt adhesive running the full perimeter of the frame on both upstream and

The EZ Flow II fiberglass media is continuous filament spun glass. A resinous bonding agent provides rigidity and resistance to media compression.





EZ Flow II Filters

Standard Sizes and Performance Data

Nominal Size (Inches)	Actual Size (Inches)	CFM @ 300 FPM	Standard Carton Qty.	Weight Per Carton (lbs.) (Fiberglass)
10 x 10 x 1	9 ⁷ / ₈ x 9 ⁷ / ₈ x ³ / ₄	200	12	2.1
10 x 20 x 1	97/8 x 195/8 x 13/16	425	12	2.9
10 x 24 x 1	9 ⁷ / ₈ x 23 ⁵ / ₈ x ³ / ₄	500	12	3.5
10 x 25 x 1	9 ⁷ / ₈ x 24 ⁵ / ₈ x ³ / ₄	525	12	3.6
10 x 30 x 1	97/8 x 295/8 x 13/16	625	12	4.2
12 x 12 x 1	11 ⁷ / ₈ x 11 ⁷ / ₈ x ¹³ / ₁₆	300	12	2.3
12 x 20 x 1	11 ⁷ / ₈ x 19 ⁵ / ₈ x ¹³ / ₁₆	500	12	3.3
12 x 24 x 1	117/8 x 235/8 x 13/16	600	12	3.7
12 x 25 x 1	117/8 x 245/8 x 3/4	625	12	3.9
12 x 30 x 1	11 ⁷ / ₈ x 29 ⁵ / ₈ x ¹³ / ₁₆	750	12	4.3
14 x 14 x 1	137/ ₈ x 137/ ₈ x ¹³ / ₁₆	400	12	2.9
14 x 20 x 1	137/ ₈ x 195/ ₈ x ¹³ / ₁₆	575	12	3.5
14 x 24 x 1	13 ⁷ / ₈ x 23 ⁵ / ₈ x ¹³ / ₁₆	700	12	3.9
14 x 25 x 1	13 ⁷ / ₈ x 24 ⁵ / ₈ x ¹³ / ₁₆	725	12	3.9
14 x 30 x 1	13 ⁷ / ₈ x 29 ⁵ / ₈ x ¹³ / ₁₆	875	12	4.6
15 x 20 x 1	14 ⁷ / ₈ x 19 ⁵ / ₈ x ¹³ / ₁₆	775	12	3.9
15 x 25 x 1	14 ⁷ / ₈ x 24 ⁵ / ₈ x ³ / ₄	625	12	4.0
15 x 30 x 1	147/8 x 295/8 x 3/4	950	12	6.5
16 x 16 x 1	15 ⁷ / ₈ x 15 ⁵ / ₈ x ¹³ / ₁₆	525	12	3.1
16 x 20 x 1	15 ⁷ / ₈ x 19 ⁵ / ₈ x ¹³ / ₁₆	675	12	3.4
16 x 221/4 x 1	15 ⁷ / ₈ x 22 ¹ / ₈ x ³ / ₄	750	12	4.6
16 x 24 x 1	15 ⁷ / ₈ x 23 ⁵ / ₈ x ¹³ / ₁₆	800	12	4.0
16 x 25 x 1	15 ⁷ / ₈ x 24 ⁵ / ₈ x ¹³ / ₁₆	825	12	4.1
18 x 20 x 1	17 ⁷ / ₈ x 19 ⁵ / ₈ x ¹³ / ₁₆	750	12	4.3
18 x 24 x 1	177/ ₈ x 235/ ₈ x ¹³ / ₁₆	900	12	4.5
18 x 25 x 1	171/8 x 245/8 x 3/4	950	12	4.5
19 x 27 x 1	187/8 x 267/8 x 3/4	1075	12	5.4
20 x 20 x 1	195/8 x 195/8 x 13/16	825	12	3.9
20 x 221/4 x 1	195/ ₈ x 221/ ₈ x 3/ ₄	950	12	4.5
20 x 24 x 1	195/8 x 235/8 x 13/16	1000	12	4.6
20 x 25 x 1	195/8 x 245/8 x 13/16	1050	12	4.7
20 x 30 x 1	195/8 x 295/8 x 13/16	1250	12	5.7
22 x 22 x 1	211/8 x 211/8 x 3/4	1000	12	5.1
24 x 24 x 1	23 ⁷ / ₁₆ x 23 ⁷ / ₁₆ x ¹³ / ₁₆	1200	12	5.4
24 x 30 x 1	23 ⁷ / ₁₆ x 29 ⁵ / ₈ x ³ / ₄	500	12	6.4
25 x 25 x 1	245/8 x 245/8 x 3/4	1300	12	5.7

Typical initial (clean) pressure drop at nominal CFM is 0.07" w.g.

Recommended final resistance is 0.50" but system design may dictate a lower changeout point.

EZ Flow® is a registered trademark of Flanders Corporation in the U.S.



AAF Flanders has a policy of continuous product research and improvement. We reserve the right to change design and specifications without notice.

©2022 AAF International and its affiliated companies.