



see what Delta can do

KITCHEN FAUCETS

■ Monrovia[™] Collection ■ Single Handle Pull-Down

FEATURES:

- DIAMOND Seal[®] Technology
- Touch-Clean[®] Technology
- MagnaTite[®] Docking System
- Lumicoat[™] Finish (-PR models only)
- Lumicoat[™] Finishes easily wipe clean without cleaners and chemicals on the products most commonly touched areas

STANDARD SPECIFICATIONS:

- Max flow rate 1.8 gpm @ 60 psi, 6.8 L/min @ 414 kPa
- One or three hole mount (8" escutcheon not included, order separately)
- Diamond coated ceramic cartridge
- 3/8" O.D. straight, staggered PEX supply lines
- Spout rotates 360°
- Hot/cold indicator markings
- Dual integral check valves in sprayer assembly
- Two-function wand; Aerated stream or spray

WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

ASME A112.18.1 / CSA B125.1 Indicates compliance to ICC/ANSI A117.1

Delta Faucet Company 55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2021 Delta Faucet Company

Designate proper finish suffix

3x 1 1/4" -1 1/2"

(32-38 mm) Hole Size

m

傡

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability. DSP-K-9191-DST Rev A

(203 mm) Centers

_ 10 3/4" (273 mm)

reder

ł

2 1/2" (64 mm) Max. Deck Thickness with 10 3/4"

(273 mm) escutcheon 3" (76 mm) all others

> 3/8' Compression Fittings

10[']1/4" (260 mm)

dt

35 3/8" (898 mm)

37 3/4" (959 mm)