

PFWSC4757S



SINGLE HANDLE LAVATORY FAUCET

- 4" centerset installation
- Max. flow rate: 1.2 gpm at 60 psi
- Metal lever handle
- Ceramic disc cartridge
- With brass pop-up
- Max deck thickness: 1-1/2"
- 30" flexible nylon Neoperl supply lines
- Brass construction
- Certified to ASME A112.18.1 / CSA B125.1
- NSF/ANSI/CAN61: Q ≤ 1
- cUPC/IAPMO listed
- WaterSense certified



PFWSC4757SCP

PFWSC4757SCP Chrome

Product Specifications

Technical drawings of the 1000 Series 1/2" x 1 1/2" x 4" 180° Swing Arm. The drawings include a front view, a side view, and a detail view of the mounting bracket. Dimensions are provided in inches and millimeters.

Front View Dimensions:

- Top width: 6 1/16" [154.0mm]
- Right side height: 1 1/2" [38.54mm]
- Bottom width: 4" [101.60mm]
- Mounting hole: 9/16"-24UNEF-2B

Side View Dimensions:

- Top width: 6 1/2" [165.69mm]
- Right side height: 4 13/16" [121.58mm]
- Mounting hole: 2 5/16" [59.3mm]

Detail View Dimensions:

- Top width: 7 15/16" [201.2mm]
- Right side height: 1 9/16" - 2 3/16" [38.2mm] - [55.1mm]
- Mounting hole: 1-1/2"-18UNEF
- Bottom width: 1 1/4" [31.8mm]
- Top hole: Ø2 1/8" [54.0mm]
- Top hole offset: 7/16" [11.8mm]

This product comes complete with installation, operating, care and maintenance instructions. This PROFLO faucet carries a limited lifetime warranty when installed in residential applications. The warranty is five years in commercial applications.

*Compliant with lead content requirements of California AB 1953.



FERGUSON.COM/PROFLO

05/24/22 Rev.A