

# XL-TRACE EDGE SELF-REGULATING HEATING CABLE

nVent RAYCHEM XL-Trace Edge self-regulating trace heating cables provide energy efficient and easy to use solutions for pipe freeze protection and flow maintenance of grease waste lines (above and below ground) and fuel lines (above ground).



## FEATURES

Simple to design

Easy to install: cut to length, meter marks, fast RayClic cold connection system

Energy efficient and safe: self-regulating cable, advanced energy saving controls, no cable overheating possible, suitable for plastic pipes

Reliable during long life: 10 year extended product warranty available, maintenance free

## SPECIFICATIONS

**Min Installation Temperature:** 0 °F

**Ground Path Type:** Braid

Table 1/2

Catalog Number	Item Name	Supply Voltage	Nominal Power Output @ 40°F, 120V	Nominal Power Output @ 40°F, 240V	Outer Jacket Material	Max Circuit Length
200002607	5XLE1-CR	120 V	5 W/ft		Modified Polyolefin	287 ft
200002608	5XLE2-CR	208 – 277 V		5 W/ft	Modified Polyolefin	584 ft
200002609	8XLE1-CR	120 V	8 W/ft		Modified Polyolefin	233 ft
200002610	8XLE2-CR	208 – 277 V		8 W/ft	Modified Polyolefin	452 ft
200002611	5XLE1-CT	120 V	5 W/ft		Fluoropolymer	287 ft
200002612	5XLE2-CT	208 – 277 V		5 W/ft	Fluoropolymer	584 ft

<b>Catalog Number</b>	<b>Item Name</b>	<b>Supply Voltage</b>	<b>Nominal Power Output @ 40°F, 120V</b>	<b>Nominal Power Output @ 40°F, 240V</b>	<b>Outer Jacket Material</b>	<b>Max Circuit Length</b>
2000002613	8XLE1-CT	120 V	8 W/ft		Fluoropolymer	233 ft
2000002614	8XLE2-CT	208 – 277 V		8 W/ft	Fluoropolymer	452 ft
P000000793	12XLE2-CR	208 – 277 V		12 W/ft	Modified Polyolefin	360 ft
P000000794	12XLE2-CT	208 – 277 V		12 W/ft	Fluoropolymer	360 ft
2000002864	3XLE1-CR	120 V	3 W/ft		Modified Polyolefin	368 ft
2000002865	3XLE2-CR	208 – 277 V		3 W/ft	Modified Polyolefin	642 ft

Table 2/2

<b>Catalog Number</b>	<b>Item Name</b>	<b>Max Continuous Exposure Temperature, Power Off</b>
2000002607	5XLE1-CR	185 °F
2000002608	5XLE2-CR	185 °F
2000002609	8XLE1-CR	185 °F
2000002610	8XLE2-CR	185 °F
2000002611	5XLE1-CT	185 °F
2000002612	5XLE2-CT	185 °F
2000002613	8XLE1-CT	185 °F
2000002614	8XLE2-CT	185 °F
P000000793	12XLE2-CR	185 °F
P000000794	12XLE2-CT	185 °F
2000002864	3XLE1-CR	185 °F
2000002865	3XLE2-CR	185 °F

## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**North America**

Tel +1.800.545.6258

Fax +1.800.527.5703

[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

**Europe, Middle East, Africa**

Tel +32.16.213.511

Fax +32.16.213.604

[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

**Asia Pacific**

Tel +86.21.2412.1688

Fax +86.21.5426.3167

[cn.thermal.info@nvent.com](mailto:cn.thermal.info@nvent.com)

**Latin America**

Tel +1.713.868.4800

Fax +1.713.868.2333

[thermal.info@nvent.com](mailto:thermal.info@nvent.com)



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**