




PRODUCT DESCRIPTION

Reeded glass tubes are paired with ribbed aluminum LED housings in a Gold finish. The interior frosted glass diffusers soften the high-powered LED boards concealed within. The low-voltage light sources are driven by a commercially rated range voltage LED drivers with universal dimming, allowing them to be used in both residential and decorative commercial or hospitality applications.



\*max overall height

MEASUREMENTS

DIMENSION : 22.5" L x 22.5" W x 17" H  
MAX OAH : 140" OAH  
CANOPY : 22.5" W x 1.5" H x 22.5" L  
HANGING WEIGHT : 37.5 lb

LAMPING

INPUT VOLTAGE : 120-277V  
LUMENS : 5,400 Rated (3,840 Del.)  
BULB : 12 x 5W LED PCB Integrated , 60W Total  
BULB INCLUDED : (Integrated)  
DIMMABLE : Only at 120V  
CRI : 90 CRI  
COLOR\_TEMP : 3000K

FINISHES OPTION

Gold

GLASS

Clear Ribbed 144

MATERIAL

Aluminum

RATINGS

cETLus  
Dry Location



ADDITIONAL

SLOPE: 30  
RATED LIFE 25000 Hours  
OPERATING TEMPERATURE:  
-20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Contemporary  
Lighting™

WESTERN DISTRIBUTION CENTER (HEADQUARTER)  
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746  
EASTERN DISTRIBUTION CENTER  
4200 SHIRLEY DR. | ATLANTA, GA 30336  
P. 626.956.4200 | F. 626.956.4225 | et2online.com