

1.0 PRODUCT DESCRIPTION

Available Sizes:

- 14 – 60"/DN350 – DN1500


Maximum Working Pressure:

- Pressure ratings for Victaulic AGS fittings conform to the ratings of the Style W07 or Style W77 couplings (refer to publications [20.02](#) or [20.03](#) for more information)

Function:

- Connects pipe, provides change in direction and adapts to sizes or components
- Supplied with Victaulic AGS grooves
- Exclusively for use with Victaulic couplings, valves, accessories and pipe which feature ends formed with the Victaulic AGS groove profile

2.0 CERTIFICATION/LISTINGS



ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.

3.0 SPECIFICATIONS – MATERIAL

Cast Fittings: Ductile iron conforming to ASTM A536, Grade 65-45-12. Ductile iron conforming to ASTM A395, Grade 65-45-15, is available upon special request.

Segmentally Welded Fittings: Fabricated from carbon steel pipe conforming to ASTM A53, Type E or S, Grade B or API-5L, PSL 1 or PSL 2.

Nipples: Carbon steel pipe conforming to ASTM A53, Type E or S, Grade B or API-5L, PSL 1 or PSL 2.

Flanged Adapter Nipples:

Flange: ASME/ANSI B16.5 raised face carbon steel slip-on flange.

Pipe: Carbon steel pipe conforming to ASTM A53, Type E or S, Grade B or API-5L, PSL 1 or PSL 2.

Fitting Coatings: (specify choice)

- ☐ Standard: Orange enamel.
- ☐ Optional: Hot dipped galvanized (ASTM A153) and others.
- ☐ Optional: Liquid Epoxy (AWWA C210)
- ☐ Optional: Fusion Bonded Epoxy (AWWA C213)
- ☐ Optional: Other coatings available, contact Victaulic for details.

Flanged Adapter Nipple Coating:

- ☐ None (Unfinished).
- ☐ Optional: Orange enamel.
- ☐ Optional: Hot dip galvanized and others.

Fitting Linings: (specify choice)


- ☐ Standard: Orange Enamel
- ☐ Optional: Hot Dip Galvanized (ASTM A153)
- ☐ Optional: Liquid Epoxy (AWWA C210).
- ☐ Optional: FBE (AWWA C213)
- ☐ Optional: Others available upon request contact Victaulic for details.

4.9 DIMENSIONS

Cap

No. W60

(Segmentally Welded Steel)



No. W60

Size		No. W60 Cap	
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight Each lb kg
14 DN350	14.000 355.6	6.50 165.0	33.2 15.1
16 DN400	16.000 406.4	7.00 178.0	41.2 18.7
18 DN450	18.000 457.0	8.00 203.0	54.6 24.8
20 DN500	20.000 508.0	9.00 229.0	67.5 30.6
24 DN600	24.000 610.0	10.50 267.0	96.0 43.5
26 DN650	26.000 660.4	14.50 368.3	144.0 65.3
28 DN700	28.000 711.2	15.00 381.0	166.0 75.2
30 DN750	30.000 762.0	15.50 393.7	187.0 84.8
32 DN800	32.000 812.8	16.00 406.4	209.0 94.8
36 DN900	36.000 914.4	17.00 431.8	253.0 114.7
40 DN1000	40.000 1016.8	18.00 457.2	391.0 177.3
42 DN1050	42.000 1066.8	18.50 469.9	420.0 190.5
46 DN1150	46.000 1168.4	19.50 495.3	532.0 241.3
48 DN1200	48.000 1219.2	20.00 508.0	613.0 278.1
54 DN1372	54.000 1371.6	21.50 546.1	785.0 356.1
56 DN1422	56.000 1422.4	22.00 558.8	875.0 396.8
60 DN1524	60.000 1524.0	23.00 584.2	977.0 443.1