

# ChoreMaster® Series

## Gasoline – Direct Drive

*The multipurpose CM Series is great for keeping patios, siding and equipment clean. Use its built-in detergent injector with a Mi-T-M cleaner to effectively remove mold, mildew and dirt.*



COLD WATER PRESSURE WASHERS

### Pump:

Equipped with the Mi-T-M Pressure Relief Start which eliminates pressure build-up in the system | Thermal relief valve | In-line water strainer | Built-in low pressure detergent injector

### Frame:

Powder coated steel frame and base plate with 1½-inch tube handles | 10-inch flat-free tires

### Unit Includes:

Quick connect nozzles - 15°, 25° and detergent nozzle | 25-foot x ¾-inch wire-braided high pressure hose (50-foot on CM-3600 and CM-4200 models) | Professional-grade trigger gun | Two-piece, 36-inch lance

### Limited Warranties:

1 year AR and Mi-T-M pumps | 1 year Mi-T-M engine

| USAGE               | Residential/Commercial | Commercial              | Commercial          | Commercial          |
|---------------------|------------------------|-------------------------|---------------------|---------------------|
| MODEL NO.           | CM-3000-0MMB           | CM-3200-0MMB (pictured) | CM-3600-0MMB        | CM-4200-0MMB        |
| PSI                 | 3000                   | 3200                    | 3600                | 4200                |
| GPM                 | 2.4                    | 2.4                     | 2.8                 | 3.4                 |
| DISPLACEMENT/ENGINE | 212cc Mi-T-M OHV       | 212cc Mi-T-M OHV        | 300cc Mi-T-M OHV    | 420cc Mi-T-M OHV    |
| PUMP                | Mi-T-M, axial          | Mi-T-M, crankshaft      | AR, crankshaft      | AR, crankshaft      |
| UNLOADER            | Fixed pressure         | Adjustable pressure     | Adjustable pressure | Adjustable pressure |
| DIMENSIONS (LxWxH)  | 37x21x24.5in.          | 37x21x24.5in.           | 40x22.5x24.5in.     | 40x22.5x24.5in.     |
| SHIP WT.            | 100 lb.                | 110 lb.                 | 180 lb.             | 192 lb.             |
| NET WT.             | 75 lb.                 | 85 lb.                  | 130 lb.             | 142 lb.             |

Consult factory for more information on these available options:

– 25-foot high pressure hose with quick connects

– 50-foot high pressure hose, with and without quick connects