

Infiniti[®] GR

Tankless Gas Condensing Water Heater

With Built-In Recirculation

Features

- ENERGY STAR[®] Qualified.
- Certified Green Product[™] by the Green Restaurant Association.
- Residential and Commercial Application.
- Indoor and Outdoor Installation (requires outdoor installation kit).
- Stainless Steel Heat Exchanger.
- Built-in Recirculation Pump and Dedicated Recirculation Connection.
- AHRI Certified.
- 0.96 UEF.



Additional Details

- **Ultra Low NOx System**—Complies with SCAQMD Rule 1146.2 for natural gas Low NOx Emissions of 14 ng/J or 20 ppm.
- **Low Lead Compliant with NSF/ANSI 372.**
- **Easy Installation Options:**
 - Compatible with 1/2" (12.7mm) Gas Pipe up to 24 ft. (7.32m).
 - Compatible with 2" (50.8mm) PVC Vent up to 60 ft. (18.3m) or 3" (76.2mm) up to 150 ft. (45.7m).
 - Vent with PVC, CPVC, Stainless Steel or Polypropylene.
 - Supports Direct Vent, Unbalanced Vent or Outdoor Vent Cap.
- **Commercial Application Features:**
 - Temperature Setting—95°F (35°C) to 185°F (85°C).
 - Cascade up to 2 Units (mix up to 14 Infiniti[®] GS units).
 - Free Standing Rack System.
 - Easy plumbing manifold kit.
 - Common venting with PVC, CPVC, or Polypropylene up to 8 units.
- **Service Friendly Features:**
 - Air Filter and Inlet Water Filter—Mounted outside of cabinet for easy access and servicing.
 - Gasket Kit Included.



15-Year Residential Heat Exchanger Warranty / 5-Year Parts Warranty.

For more information on warranty, please visit www.bradfordwhite.com

For products installed in USA, Canada, and Puerto Rico. See complete copy of the warranty included with the heater for limitations.

Infiniti® GR

Tankless Gas Condensing Water Heater With Built-In Recirculation



SPECIFICATIONS

These water heaters meet or exceed all or portions of (where applicable) the minimum efficiency requirements of ASHRAE Standard 90.1 (latest edition).

Model	Configuration	Gas Type	Max. Input		Min. Input		Turndown Ratio	Uniform Energy Factor
			MBH	kW	MBH	kW		
RTGR199N1	Recirculation	Natural Gas	199	58.3	13	3.8	15:1	0.96
RTGR199X1	Recirculation	Propane	199	58.3	13	3.8	15:1	0.96
Model		Water Connection Size	Gas Connection Size		Product Weight lbs.	Shipping Weight kg.		
RTGR199N1		3/4" NPT	3/4" NPT		85	39	96	44
RTGR199X1		3/4" NPT	3/4" NPT		85	39	96	44

DOMESTIC HOT WATER CAPACITY

Flow Rate at Degree Rise														Minimum Water Flow									
40°F	50°F	60°F	70°F	80°F	90°F	100°F	110°F	120°F	130°F	140°F	GPM	LPM	GPM	LPM									
9.7	36.7	7.8	29.5	6.5	24.6	5.6	21.2	4.9	18.5	4.3	16.3	3.9	14.8	3.5	13.2	3.2	12.1	3.0	11.4	2.8	10.6	0.5	1.9

CLEARANCES

Location	For Installation From Non-Combustible and Combustible Surfaces		Suggested Service Clearances	
	in.	cm.	in.	cm.
Top	10	25	18	46
Back	1	2.5	1	2.5
Front	4	10	40	101
Side	4	10	8	20
Bottom	10	25	24	61

ELECTRICAL DATA

Model	Power Supply		Standby	Power Consumption	
	Main Supply	Max Current		Operation	Anti Freeze
RTGR199N1	120V 60Hz	Less than 2A	2.7W	188W	117W
RTGR199X1	120V 60Hz	Less than 2A	2.7W	188W	117W

VENTING SYSTEM

2" (50.8mm) Combustion Air / Vent Pipe		3" (76.2mm) Combustion Air / Vent Pipe	
Maximum Equivalent Length*	Maximum Number of Elbows	Maximum Equivalent Length*	Maximum Number of Elbows
ft.	m.	ft.	m.
60	18	5	150
		45	
			8

* For each elbow, reduce maximum allowable length:


5 ft (1.5m) for each 3" 90° elbow 8 ft (2.4m) for each 2" 90° elbow
3 ft (0.9m) for each 3" 45° elbow 4 ft (1.2m) for each 2" 45° elbow

SAMPLE SPECIFICATION

Condensing gas tankless wall-mounted water heater(s) shall be Infiniti® GR Series model _____, which are certified by ETL to the latest edition of ANSI standard Z21.10.3/CSA 4.3. This water heater shall have a built-in digital control for temperature adjustment. This water heater shall have a built-in recirculation pump and dedicated recirculation connection. Water heater(s) shall be designed to burn natural gas or propane. Water heater(s) with rated input of _____ BTU/Hr. (kW) shall have a nominal flow rate capacity of _____ GPM/GPH (LPM/LPH) at _____ °F (°C) rise. Water heater(s) shall have a 15:1 Turndown ratio. Water heater(s) is rated for 150 PSI (1034 kPa) working pressure and 300 PSI (2068 kPa) test pressure. Natural gas supply pressure shall be 3.5" (89mm) to 10.5" (267mm) WC and propane gas supply pressure shall be 8.0" (203mm) to 14.0" (356mm) WC. The minimum input for natural gas and propane shall be 13,000 BTU/Hr. (3.8kW). Water heater(s) shall have a dual heat exchanger with stainless steel primary and secondary. Water heater(s) shall have 3/4" (19mm) inlet gas connection with flexibility of utilizing a 1/2" (12.7mm), 3/4" (19mm) or 1" (25.4mm) gas line. Water heater shall have a filtered 3/4" (19mm) inlet and 3/4" (19mm) outlet water connections. Indoor installation model shall have the water connection on the bottom of the heater. Outdoor installation should be available with the outdoor installation kit. Water heater(s) shall be vented with 2" (50.8mm) PVC/CPVC/polypropylene vent pipe at a distance not to exceed 60 ft. (18.3m) (or equivalent) with each elbow equal to 8 ft. (2.4m) of pipe length or 3" (76.2mm) PVC/CPVC/polypropylene vent pipe at a distance 150 ft. (45.7m) (or equivalent) with each elbow equal to 5 ft. (1.5m) of pipe length. Water heater(s) shall have 15-year limited Heat Exchanger warranty and 5-year limited Parts warranty (8-year Heat Exchanger and 5-year Parts for commercial use) per Bradford White Limited Warranty.

DIMENSIONAL DATA

Recirculation Model RTGR199N1 and RTGR199X1		
Location	Description	Size
A	Exhaust	2" PVC
B	Air Intake	2" PVC
C	Hot Water Connection	3/4" NPT
D	Condensate	1/2" NPT
E	Recirculation Return Connection	3/4" NPT
F	Cold Water Connection	3/4" NPT
G	Gas	3/4" NPT
H	Cold Water Filter	—
I	Recirculation Return Filter	—



Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.



Sales: 800-523-2931

24/7 Technical Support: 800-334-3393 • Email TechServ@bradfordwhite.com

©2024, Bradford White Corporation, USA. All rights reserved.

BRADFORD WHITE IS —



1156-1224