


ME by Starck Toilet wall-mounted HygieneFlush ♿ # 257909..92 / 257909..92

| < 14 1/2" Inch > |



Toilet wall-mounted HygieneFlush	Dimension	Weight	Order number
rimless, washdown model, Rotationflush, Durafix included, WaterSense® listed, cUPC® listed*			
Colors			
20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness) 90 White HygieneGlaze/White Satin Matte			
Variant			
♣ inside color White with HygieneGlaze, outside color White, 1.28/0.8 gpf	14 1/2" x 22 1/2" Inch	59.5 lb	257909..92
♣ inside color White with HygieneGlaze, outside color White Satin Matte, 1.28/0.8 gpf	14 1/2" x 22 1/2" Inch	59.5 lb	257909..92
Infobox			
Durafix for concealed installation is included, Not available with WonderGliss, In-wall tank & carrier and actuator plate required for installation, Wall-mounted toilet is ADA compliant, when installed with a seat height of 17" - 19" from the finished floor, * Complies with following standards: ASME A112.19.2/CSA B45.1 and ASME A112.19.14			
Accessory for ceramics			
Toilet seat and cover removable, hinges stainless steel, with slow close		4.6 lb	002009
Toilet seat and cover hinges stainless steel, without slow close		4.6 lb	002001
Hardware for wall-mounted bidet and wall-mounted toilet	Ø 1/2" x 7 1/8" Inch	0.4 lb	006500
Noise reduction gasket			Schallschutz-Set 005090
Actuator plate A1, for toilet, plastic mechanical actuation, for surface mounted installation, dual flush, mounting frame, mounting hardware included, push rods, front plate plastic	8 1/2" x 5 3/4" Inch	0.7 lb	WD5008

ME by Starck Toilet wall-mounted HygieneFlush  # 257909..92
/ 257909..92

|< 14 1/2" Inch >|

<p>Toilet in-wall tank & carrier, Standard WaterSense® listed, For 2"x4" and 2"x6" wall installation, for toilets with a projection of <= 24 5/8", adjustable feet 0" - 9 1/2", SensoWash ready, mechanical front flush actuation, includes in-wall tank, marking of filling height, dual flush, insulated against condensation, Scope of delivery, HDPE wall-mounted toilet connection bend DN 90/90, PE wall-mounted toilet connection set DN 90, wall-mounted mounting rods M12, mounting hardware included, 2 bolt caps, cUPC® listed*, Load capacity = 880 lbs</p>	<p>23 1/4" x 45 1/4" Inch 35.3 lb</p>	<p>WD1022</p>
--	---------------------------------------	---------------

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.