
Location: _____

MIFAB® T100-PGE-4

Ductile Iron Slotted Grate to suit 4" clear opening channels

Specification: T100-PGE-4 ductile iron slotted grates are independently certified to meet Load Class E tested in accordance with EN 1433 134,800 lbs. 600kN. The grate length is 19.69" (.50 m). The grates utilize the patented "Clipfix" grate locking mechanism. The system (channel and grate) provides longitudinal shift protection.








CLIPFIX ADVANTAGE
The MEA polymer concrete and GRP channels are designed for our universal CLIPFIX grate locking mechanism. The system (channel and grate) provides longitudinal shift protection.

Grate Free Area
T100-PGE-4
19.49 Sq. in./ft.



GRATE MODEL NUMBER	LENGTH
T100-PGE-4	19.69" (500 mm)

LOAD CLASS E

MEA BUILDING SUCCES

EN 1433
134,800 LBS.,
600kN, 2,785 PSI

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____ Page No: _____
Section No: _____ Contractor: _____
Schedule No: _____ Purchase Order No: _____

MIFAB® *reserves the right to make changes in material and design without formal notice and obligation.*

USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880