



# Time-Delay, Current-Limiting 250 Volts, 3 $\frac{1}{10}$ -200 Amps

HAC-R



## Dimensional Data



## General Information:

- A general purpose 250 Volt AC time-delay cartridge fuse for residential and light-duty motor protection.
- The HAC-R fuse has the same physical dimensions as the Class R fuses.

## Electrical Ratings (Catalog Symbol and Amperes)

250 Volts		
HAC-R-3 $\frac{1}{10}$	HAC-R-25	HAC-R-60
HAC-R-5	HAC-R-30	HAC-R-70
HAC-R-6 $\frac{1}{2}$	HAC-R-35	HAC-R-80
HAC-R-10	HAC-R-40	HAC-R-100
HAC-R-15	HAC-R-45	HAC-R-125
HAC-R-20	HAC-R-50	HAC-R-200

## Catalog Symbol: HAC-R

Time-Delay, Current-Limiting

Ampere Rating: 3 $\frac{1}{10}$  to 200 Amperes

Voltage Rating: 250 Volts (or less)

## Agency Approvals:

UL Listed, UL248-12, 250 VAC/125 VDC,  
Guide JDDZ, File E4273CSA Certified, C22.2 No. 248.12,  
250 VAC, Class 1422-02, File 53787

## Carton Quantity and Weight

Catalog Number	Carton Specifications							
	Shelf Pack				Master Pack			
	Qty.	Size	Cu. In.	Wt. (Lbs.)	Qty.	Size	Cu. In.	Wt. (Lbs.)
HAC-R-3 $\frac{1}{10}$	10	3" x 2 $\frac{1}{4}$ " x 1 $\frac{1}{4}$ "	8.4	0.4	100	6 $\frac{1}{2}$ " x 4 $\frac{1}{8}$ " x 3"	90.2	5.5
HAC-R-5								
HAC-R-6 $\frac{1}{2}$								
HAC-R-10								
HAC-R-15								
HAC-R-20								
HAC-R-25								
HAC-R-30								
HAC-R-35								
HAC-R-40								
HAC-R-45	10	4 $\frac{1}{2}$ " x 3 $\frac{1}{4}$ " x 3 $\frac{3}{4}$ "	51.8	1.0	100	9 $\frac{1}{4}$ " x 6 $\frac{1}{4}$ " x 4 $\frac{1}{4}$ "	265.4	12.5
HAC-R-50								
HAC-R-60								
HAC-R-70								
HAC-R-80	5	5 $\frac{3}{4}$ " x 1 $\frac{1}{4}$ " x 6 $\frac{3}{8}$ "	45.8	1.5	—	—	—	—
HAC-R-100								
HAC-R-125	1	7 $\frac{1}{2}$ " x 2" x 2"	30.0	0.874	—	—	—	—
HAC-R-200								

The only controlled copy of this BIF document is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

