PF92260

Automatic Sump Pumps

Product Features


- 1/4 HP thermoplastic automatic sump pump with vertical float
- Submersible sump pump for typical residential applications
- Comes with 10' power cord with piggyback plug (on switch cord)
- 3.8 amps, 370 watts
- Maximum head of 25 feet
- Maximum flow rate of 30 GPM

- 3450 RPM
- · Permanent split capacitor motor
- SJE Rhombus vertical float switch
- Liquid temperature range 32°-120°F
- Discharge size 1-1/4" MNPT & 1-1/4" FNPT
- Handles 1/8" solids





PROFLO.




Performance Chart


Discharge Height	0'	5'	10'	15'	20'	25'
Gallons per Minute	30	22	20	16	9	2
Gallons per Hour	1800	1320	1200	960	540	120

Warranty and Codes

These products come complete with installation, operating care and maintenance instructions. In an effort to continually improve our products, FEI will make design changes from time to time. We reserve the right to ship newly designed products to fill any order unless we agree in writing to do otherwise. PROFLO Pumps carry the following limited warranty:

- Cast Iron & Utility Pumps 3-year limited warranty
- Thermoplastic Sump & Utility Pumps 1-year limited warranty
- Sewage & Effluent Pumps 1-year limited warranty







Product Specifications